



İMALAT BÜLTENİ PRODUCT DATA SHEET PRODUKT INFORMATION



RECOMPOUND SERIES

RECOMPOUND SERIES oils are special closed system gear oils that can work under heavy loads.

RECOMPOUND SERIES contain EP additives to minimize the wear and other additives against oxidation and foam formation.

RECOMPOUND SERIES do not affect the sealing.

RECOMPOUND SERIES protect gears rusting and corrosion even if existence of water in the system.

RECOMPOUND SERIES prevent deposits formation due to its special antioxidants.

RECOMPOUND SERIES provide elongated service life thanks to its resistance to oxidation.

PERFORMANCE:

AGMA 250.04
US STEEL 224

STORAGE CONDITIONS:

Protect against direct sunlight and rain. Recommended storage temperature is between (+5) - (+35) °C.

“The above information is derived from our quality checks. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. “

01.2007.05.11

Yukarıda belirtilen değerler son bilgilerdir. Yeni gelişmelere göre firmamız tarafından değiştirilebilir.

BELGİN MADENİ YAĞLAR TİCARET VE SANAYİ A.Ş.

TELEFONLAR: (0262) 751 02 92 (PBX)-751 01 90 FAX: (0262) 751 01 98-751 06 67

E-MAIL: lojistik@belginoil.com WEB SİTE: <http://www.belginoil.com>

GOSB-Gebze Organize Sanayi Bölgesi



İMALAT BÜLTENİ PRODUCT DATA SHEET PRODUKT INFORMATION



RECOMPOUND SERIES

| TECHNICAL PROPERTIES | TEST VALUES | | | | | | | | TEST METHOD | |
|---|----------------|----------------|----------------|---------------|---------------|---------------|---------------|---------------|----------------|----------------|
| | 46 | 68 | 100 | 150 | 220 | 320 | 460 | 680 | | 1000 |
| Density (20°C, g/cm ³) | 0,880 ±0,02 | 0,885 ±0,02 | 0,895 ±0,02 | 0,90 ±0,02 | 0,90 ±0,02 | 0,90 ±0,02 | 0,91 ±0,02 | 0,91 ±0,02 | 0,92 ±0,02 | ASTM D 1298 |
| Kinematic Viscosity (40°C, cSt) | 41,4- 50,6 | 61,2- 72,8 | 90-110 | 135- 165 | 198- 242 | 288- 352 | 414- 506 | 612- 728 | 900- 1100 | ASTM D 445 |
| Viscosity Index (min) | 95 | 95 | 92 | 92 | 90 | 90 | 85 | 85 | 80 | ASTM D 2270 |
| Flash Point (°C, min.) | 220 | 230 | 240 | 245 | 250 | 250 | 260 | 260 | 270 | ASTM D 92 |
| Pour Point (°C, max) | -30 | -30 | -24 | -24 | -18 | -12 | -9 | -9 | -6 | ASTM D 97 |
| Foaming Tendency/Stability (2.kd, 93,5°C, mL) | 50/0 | | | | | | | | ASTM D 892 | |
| Rust Preventive Properties | Pass | | | | | | | | ASTM D 665B | |
| Water Separability | 40/37/3 | | | | | | | | ASTM D 1401 | |

“The above information is derived from our quality checks. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose.”

01.2007.05.11

Yukarıda belirtilen değerler son bilgilerdir. Yeni gelişmelere göre firmamız tarafından değiştirilebilir.

BELGİN MADENİ YAĞLAR TİCARET VE SANAYİ A.Ş.

TELEFONLAR: (0262) 751 02 92 (PBX)-751 01 90 FAX: (0262) 751 01 98-751 06 67

E-MAIL: lojistik@belginoil.com WEB SİTE: <http://www.belginoil.com>

GOSB-Gebze Organize Sanayi Bölgesi