



İMALAT BÜLTENİ PRODUCT DATA SHEET PRODUKT INFORMATION



BELGEAR HYPOID SERIES

BELGEAR HYPOID SERIES; high performance gear oils for automotive transmission, differential boxes and rear axles.

BELGEAR HYPOID SERIES; protect components through a wide temperature range.

BELGEAR HYPOID SERIES; suitable for all applications where EP gear oil with limited slip performance is required.

TECHNICAL PROPERTIES	TEST VALUES			TEST METHOD
SAE	80W-90	85W-90	85W-140	-
Viscosity (100 ⁰ C, cSt)	13,5-18,5	13,5-18,5	24,0-32,5	ASTM D 445
Viscosity index (min.)	90	90	90	ASTM D 2270
Flash Point (°C, min.)	200	210	220	ASTM D 92
Pour Point (°C)	-24	-21	-12	ASTM D 97

PERFORMANCE LEVEL :

API GL-5
MIL L -2105 D

RECOMMENDED STORAGE CONDITIONS :

Protect from direct sunlight and rain. Store in the original closed drums at (+2) – (+40)°C.

“The above information is derived from our quality checks. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose.”

01.2008.02.29

Yukarıda belirtilen değerler son bilgilerdir. Yeni gelişmelere göre firmamız tarafından değiştirilebilir.

BELGİN MADENİ YAĞLAR TİCARET VE SANAYİ A.Ş.

TELEFONLAR: (0262) 751 02 92 (PBX)-751 01 90 FAX: (0262) 751 01 98-751 06 67

E-MAIL: lojistik@belginoil.com WEB SİTE: <http://www.belginoil.com>

GOSB-Gebze Organize Sanayi Bölgesi