



İMALAT BÜLTENİ PRODUCT DATA SHEET PRODUKT INFORMATION



BELGEAR SERIES

BELGEAR SERIES; are gear oils which are produced with paraffinic base oils blended with anti-corrosion additives and are designed for the utilization of differential, gearbox and hypoid gears under medium conditions.

BELGEAR SERIES are utilized in trucks, buses, automobiles and construction equipment which operate under high velocity torque, low velocity-high torque conditions.

TECHNICAL PROPERTIES	TEST VALUES			TEST METHOD
SAE	80	90	140	-
Viscosity (100°C, cSt)	7,0-11,0	13,5-18,5	24,0-32,5	ASTM D 445
Viscosity index (min.)	95	92	90	ASTM D 2270
Flash Point (°C, min.)	180	190	250	ASTM D 92
Pour Point (°C)	-24	-12	-9	ASTM D 97

PERFORMANCE LEVEL :

API GL-1

RECOMMENDED STORAGE CONDITIONS :

Protect from direct sunlight and rain. Store in the original closed drums at (+2) – (+40)°C.

“The above information is derived from our quality checks. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose.”

00.2008.06.06

Yukarıda belirtilen değerler son bilgilerdir. Yeni gelişmelere göre firmamız tarafından değiştirilebilir.

BELGİN MADENİ YAĞLAR TİCARET VE SANAYİ A.Ş.

TELEFONLAR: (0262) 751 02 92 (PBX)-751 01 90 FAX: (0262) 751 01 98-751 06 67

E-MAIL: lojistik@belginoil.com WEB SİTE: <http://www.belginoil.com>

GOSB-Gebze Organize Sanayi Bölgesi