

## Broil VGT

**Broil VGT**, refined vegetable oil which could be used in manufacturing process of edible oils for human consumption. This product provides a perfect starting raw material for high quality oils.

### TECHNICAL PROPERTIES

Characteristics	Test Methods	Typical Values
Appearance	ASTM D 4176/1	C&B
Density @ 15 °C, g/ml	ASTM D 1298	0.920
Kinematic Viscosity @ 40 °C, cSt	ASTM D 445	25-50
Flash Point COC, °C	ASTM D 92	330
Pour Point, °C	ASTM D 97	-12
Color, ASTM	ASTM D 1500	L0.5
Refractive Index @ 20 °C	ASTM D 1218	1.475

\* The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modification is reserved.

### HEALTH & SAFETY

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet.

### PACKAGING

15 kg pail, 185 kg steel drums.

\*Revision Date/No:19.09.2011/01

Production : Arslanbey Yolu Cuhane Cad. No:181  
Kartepe/Kocaeli

Tel : +90 262 3735730  
Fax : +90 262 3735575  
Internet : [www.petroyag.com](http://www.petroyag.com)  
E-mail : [info@petroyag.com](mailto:info@petroyag.com)

