



İMALAT BÜLTENİ PRODUCT DATA SHEET PRODUKT INFORMATION



CUP GREASE SERIES

CUP GREASE SERIES, is calcium soap based, red colored grease, which is used in low load and temperature.

CUP GREASE SERIES, provides excellent protection against rust and corrosion and resists water wash-out which makes them particularly suitable for equipment where moist or wet conditions are common.

The recommended operating temperature range is from -10°C to 60°C.

TECHNICAL PROPERTIES	TEST VALUES			TEST METHOD
	1	2	3	
NLGI	1	2	3	-
Color	Red			-
Soap Type	Calcium			-
Worked Penetration (25°C,60 stroke)	310-340	265-295	220-250	ASTM D 217
Dropping Point (°C)	min. 80	min. 85	min. 90	ASTM D 566
Oil Separation (%) (40°C, 18 h)	max 6	max 6	max 5	IP 121

STORAGE TEMPERATURE:

Store in the original closed drums at (+5) – (+40) °C.

“The above information is derived from our quality checks. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose.”

00.2006.06.28

Yukarıda belirtilen değerler son bilgilerdir. Yeni gelişmelere göre firmamız tarafından değiştirilebilir.

BELGİN MADENİ YAĞLAR TİCARET VE SANAYİ A.Ş.

TELEFONLAR: (0262) 751 02 92 (PBX)-751 01 90 FAX: (0262) 751 01 98-751 06 67

E-MAIL: lojistik@belginoil.com WEB SİTE: <http://www.belginoil.com>

GOSB-Gebze Organize Sanayi Bölgesi