



İMALAT BÜLTENİ PRODUCT DATA SHEET PRODUKT INFORMATION



GRESON LIT EP GREASES

GRESON LIT EP GREASES, are lithium soap greases blended with mineral oils and enriched with extreme pressure additives.

GRESON LIT EP GREASES, are long-life multipurpose industrial greases, that are resistant to water, corrosion and oxidation.

GRESON LIT EP GREASES, can be used in medium and high loading bearings, vertical shaft applications, electrical motors and also in automotive applications.

TECHNICAL PROPERTIES	TEST LIMITS						TEST METHODS
	000	00	0	1	2	3	
Soap Type	LITHIUM						-
Soap Content (%), min	5	5	5	6	8	10	ASTM D 128
Worked Penetration (25°C, 60 darbe)	445-475	400-430	355-385	310-340	265-295	220-250	ASTM D 217
Dropping Point (°C), min	140	150	160	180	185	190	ASTM D 566
Oil Separation (°C, 18 saat), max	10	10	8	6	5	4	IP 121
Anticorrosion Properties	Pass- No Corrosion						ASTM D 1743
Four Ball Welding Load (kg), min	280						ASTM D 2596

STORAGE TEMPERATURE :

Store in the original closed packaging at (+5) – (+30) °C.

“The above information is derived from our quality checks. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose.”

00.2004.11.14

Yukarıda belirtilen değerler son bilgilerdir. Yeni gelişmelere göre firmamız tarafından değiştirilebilir.

BELGİN MADENİ YAĞLAR TİCARET VE SANAYİ A.Ş.

TELEFONLAR: (0262) 751 02 92 (PBX)-751 01 90 FAX: (0262) 751 01 98-751 06 67

E-MAIL: lojistik@belginoil.com WEB SİTE: <http://www.belginoil.com>

GOSB-Gebze Organize Sanayi Bölgesi