



İMALAT BÜLTENİ PRODUCT DATA SHEET PRODUKT INFORMATION



LUBEX KM SERIES

LUBEX KM SERIES, are formulated with high viscosity index paraffinic base oils.

LUBEX KM SERIES, contains high performance additives that are protection against oxidation and corrosion.

TECHNICAL PROPERTIES	Kinematic Viscosity (100°C, cSt)	Viscosity Index (min)	Flash Point (°C, min.)
TEST METHOD	ASTM D 445	ASTM D 2270	ASTM D 92
LUBEX KM 10 W	min. 4,1	95	220
LUBEX KM 30	9,3-12,5	95	240
LUBEX KM 40	12,5-16,3	95	250
LUBEX KM 50	16,3-21,9	95	260

PERFORMANS LEVEL :

API : SC / CC
MIL-L 2104 B

STORAGE :

Protect from direct sunlight and rain. Store in the original closed drums at (+2) – (+40) °C

“The above information is derived from our quality checks. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose.”

00.2003.08.05

Yukarıda belirtilen değerler son bilgilerdir. Yeni gelişmelere göre firmamız tarafından değiştirilebilir.

BELGİN MADENİ YAĞLAR TİCARET VE SANAYİ A.Ş.

TELEFONLAR: (0262) 751 02 92 (PBX)-751 01 90 FAX: (0262) 751 01 98-751 06 67

E-MAIL: lojistik@belginoil.com WEB SİTE: <http://www.belginoil.com>

GOSB-Gebze Organize Sanayi Bölgesi