

LUBEX STOU SERIES

HIGH PERFORMANCE ENGINE OIL FOR AGRICULTURAL VEHICLES

Product Description

LUBEX STOU SERIES are multigrade motor oil, produced by blending the high viscosity index mineral base oils with anti-oxidant, anti-wear and detergent/dispersant additives.

Application/Usage

They can be used in the crankcase, transmission, hydraulic and wet-brake system of tractors. They have been specially designed for use in agricultural vehicles.

Advantages/Benefits

- Provides constant lubrication in any road and climate conditions. Therefore it can be safely used in four seasons,
- Improves the performance of the engine, does not cause oil pressure drop,
- Prevent sludge and soot accumulation in engine due to its detergent/dispersant additive,
- Prevents wear, corrosion, oxidation and foam formation,

- Provide economical advantage in engines which have frequent oil change intervals.

Specifications/Approvals

API SF/CF-4, API GL-4,
MB 227.1/228.1,
ALLISON C4,
ZF TE ML 06,
MF M1135, M1139, M1143, M1144,
FORD M2 C 159 B,
JOHN DEERE J20C, J27

Storage

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TEST VALUES			TEST METHOD
	15W 30	15W 40	20W 40	
Kinematic Viscosity (100 ⁰ C, cSt)	9,3-12,5	12,5 - 16,3	12,5 -16,3	ASTM D 445
Viscosity Index	135	130	120	ASTM D 2270
Flash Point (°C)	220	238	246	ASTM D 92
Pour Point (°C)	-15	-12	-12	ASTM D 97

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

00.2011.07.20

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.

Gebze Organize Sanayi Bölgesi (GOSB), İhsan Dede Cad. No: 125,
P.K. 1003, 41480 Gebze - Kocaeli/TURKEY
Tel: +90 262 751 02 92 PBX Faks: +90 262 751 01 98
e-mail: info@belginoil.com www.belginoil.com

