

## FM Synth Grease 2/3

**FM Synth Grease 2/3** is food grade grease produced by using anhydrous calcium soaps and pharmaceutical synthetic base oils designed to lubricate food machineries.

**FM Synth Grease 2/3** contains antioxidants, corrosion inhibitors EP/AW additives. The thickener, together with the special synthetic base oil, makes the product suitable for lubrication in applications where is the possibility of incidental or accidental food contact possible.

**FM Synth Grease 2/3** is high performance universal food machinery Grease. Its unique properties make it suitable for various types of bearing applications including heavy load conditions.

**FM Synth Grease 2/3** has NSF H1 registration (R.N: 142096).

### TECHNICAL PROPERTIES

Properties	Test Methods	Typical Values
Color	-	White
NLGI Grade	ASTM D 217	2.5
Thickener Type	-	Anhydrous Calcium
Dropping Point, °C	ASTM D566–76	> 150
Base Oil Viscosity @ 40 °C, (cSt)	ASTM D 445	180
Water Washout @ 38 °C	ASTM D 1264	% 1
Working Temperature Range, °C	-	- 20 + 120 (max. 125°C)

\* The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modification is reserved.

### HEALTH & SAFETY

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet.

### PACKAGING

400 gr cartridge, 16 kg pail.

\*Revision Date/No:29.11.2010/01

Production : Arslanbey Yolu Cuhane Cad. No:181  
Kartepe/Kocaeli

Tel : +90 262 3735730  
Fax : +90 262 3735575  
Internet : [www.petroyag.com](http://www.petroyag.com)  
E-mail : [info@petroyag.com](mailto:info@petroyag.com)

