

## Porcus CS 717

**PORCUS CS 717**, is a silicon free spin finish yarn oil developed especially to use in the production of PP and poly ethylene yarns.

### ADVANTAGES

- Due to its high thermostability prevents the formation of deposits on godets.
- During the production of yarns or subsequent operations provides excellent yarn drawing performances thanks to its superior cohesion power between yarn and reel.
- Prevents the formation of smoke during operation.
- Provides cleaner operation environment.

### TECHNICAL PROPERTIES

Property	Test Methods	Typical Values
Color	ASTM D 1500	L0.5
Density @ 15 °C, g/ml	ASTM D 4052	0.865
Kinematic Viscosity @ 40 °C, cSt	ASTM D 445	84
Flash Point (COC), °C	ASTM D 92	180
Pour Point, °C	ASTM D 97	-12
Refractive Index @ 20 °C	ASTM D 1218	1.476

\* The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modification is reserved.

### USAGE

Developed to use as a neat oil. Not recommended for use as emulsion with water. It is not miscible with water.

### HEALTH & SAFETY

- For information on the safe handling and use of this product, refer to its Material Safety Data Sheet.

### PACKAGING

180 kg drum, 850 kg IBC.

\*Revizyon Tarihi/No:26.04.2011/00

Üretim : Arslanbey Yolu Cuhane Cad. No:136  
Kartepe/Kocaeli

Tel : +90 262 3735730  
Fax : +90 262 3735575  
Internet : [www.petroyag.com](http://www.petroyag.com)  
E-mail : [info@petroyag.com](mailto:info@petroyag.com)

